

MS100XX AIBOX Enterprise Series

16-Bay H.265 4K AI Professional AI Full Feature Video Manager and Recorder



Features

High-performance, High-capacity

- H.265 supported
- 4 x 4K@30fps / 16 x 1080p@30fps video decoding capability
- Up to 64 channel
- Up to 420Mbps incoming bandwidth
- 384Mbps output bandwidth
- 16 user access simultaneously
- Max. 16 HDDs up to 128TB storage
- IPSAN storage supported

AI

- Supports deep learning algorithm
- Supports up to 50,000 face detection comparison library
- Real-time multiple face matching
- Supports searching picture by face picture

Easy to install

- Auto network organizing
- Built-in DHCP server

High reliability

- Embedded Linux
- RAID 0/1/5/6/10
- Redundant Power Supply (optional)
- Supports Automatic Network Replenishment (ANR)
- Supports Packet Loss Recovery (PLR)

Abundant functions and features

- HDMI/VGA simultaneously output different content
- E-Map, TV-Wall supported
- Bi-directional audio, Broadcasting
- NAT
- Alarm management
- Free CMS (V Station), supports 128 NVR simultaneously
- CMS supports 6 screens simultaneously (4 x Live viewing, 1 x E-Map, 1 x TV-Wall)

Specifications

	MS10016FR-16AIH	MS10032FR-16AIH	MS10064FR-16AIH
Video/Audio Input			
IP Camera Input	16 channel	32 channel	64 channel
Resolution	8MP(4K), 6MP, 5MP, 4MP, 3MP, 1080p, UXGA, 960p, 720p, XGA, SVGA, D1, CIF, QCIF		
Compression	H.265 / H.264		
Protocols	Onvif, RTSP, MoviSight		
Bit rate	64kbps ~ 16384kbps		
Incoming Bandwidth	160Mbps	320Mbps	420Mbps
Live Viewing			
Local Display	2 x HDMI, 1 x VGA, simultaneously output different content		
Multi Screen Display Local monitor(Main / Secondary):	1/1, 4/4, 1+5/1+5, 1+7/1+7, 9/9, 16/16		
Multi Screen Display Client	up to 4 screen simultaneously: 1 ~ 64 Multiple Layouts		
E-Map Function	Live Viewing in E-Map (V Station) E-PTZ / Scheme (V Station)		
Recording			
Resolution	8MP(4K), 6MP, 5MP, 4MP, 3MP, 1080p, UXGA, 960p, 720p, XGA, SVGA, D1, CIF, QCIF		
Mode	Manual / Continuous / Schedule / Event (Pre / Post)		
Event Trigger	Supported		
Tag	Supported		
Reliability	Automatic Network Replenishment (ANR)		
Search & Playback			
Search Mode	Date and time (Calendar) / Event		
Resolution	8MP(4K), 6MP, 5MP, 4MP, 3MP, 1080p, UXGA, 960p, 720p, XGA, SVGA, D1, CIF, QCIF		
Playback(Local Monitor)	4 x 4K@30fps / 16 x 1080p@30fps		
Playback(Client)	up to 16 x 4K@30fps		
Synchronize Playback (Local Monitor)	4 x 4K@30fps / 16 x 1080p@30fps		
Synchronize Playback (Client)	up to 16 x 4K@30fps		
Function	Slow forward / Fast forward / Loop / Single frame / E-PTZ / Slice playback		
Storage			
Max. Internal HDDs	16x 3.5" HDD		
RAID	Max. 128TB (up to 8TB/each) RAID 0/1/5/6/10		
External Function	IPSAN (iSCSI), up to 10 x IPSAN, Max. 100T (optional) Disk group / Quota / Disk dormancy		
Audio			
Compression	G.711a / G.711u / ADPCM / G.722 / G.722.1c / AAC-LC		
Bit rate	32kbps ~ 64kbps		
Audio Function	Bi-directional audio / Dumb / Mute / Broadcasting		
Alarm			
Service Alarm Triggers	Alarm input / Video lost / Motion detection / Tampering / Guard line / Defocus / Scene change / Enter guard area / Exit guard area / Object left / Object removal / Gathering / Audio surge / Face matching		
System Alarm Triggers	Device disconnected / No disk / Disk error / IP Address conflict / Network disconnected / Low speed / Insufficient recording space / MAC address conflict / Insufficient Snapshot storage space		
Alarm Events	Snapshot / Recording / PTZ preset / Buzzer / Email / Link to Client / Alarm caption / Live view in first window / Link to TV Wall / Link to secondary screen / Full screen viewing		
AI			
Face Matching	Real-time / Post-event		
Search Mode	Date and time / Camera / Face image		
People Counting	Supported		
Maximum Number Of Recognitive Camera	up to 4		
Face Picture Library	32 libraries Up to 50,000		
System			
Operating System	Embedded Linux		
User Management	Admin / User		
Log Management	User login / User operation / Alarm / Backup / Update		
Application Programming	Master ViewStation SDK		
Network			
Network Protocols	TCP/IP, UDP, HTTP, DHCP, DNS/DDNS, RTP/RTCP, RTSP, PPPoE, FTP, SNTp, VSIP, UPNP, SMTP, IPv4, IPv6 (optional)		
Viewer Software	CMS (NVR Station) / Web / iOS app / Android app		
Max. User Access	16 Users		
Output Bandwidth	384Mbps		
Function	NAT / Multiple network access / Packet loss recovery / Auto network organizing		
Network Test	Supported		
Interfaces			
Ethernet	3 x Gigabit network port, RJ45 interface		
Video Out	2 x HDMI (up to 3840 x 2160@60Hz) 1 x VGA (up to 1920 x 1080@60Hz)		
Audio In / Out	1 x RCA Line in / 1 x RCA Line out		
Alarm In / Out	2 x Inputs / 2 x Outputs		
Control	1 x RS485, 1 x RS232		
USB	2 x USB2.0, 2 x USB3.0		
Environmental			
Operating Temperature	-10°C ~ 55°C / 14°F ~ 131°F		
Operating Humidity	10% ~ 85%		
Electrical			
Power	100 ~ 240V AC, 50 ~ 60Hz		
Power Consumption	Max. 150W (HDD not included)		
Mechanical			
Weight	20kg / 44lb (HDD not included)		
Dimensions	483 x 500 x 156mm / 19.02" x 19.69" x 6.14"		

Dimensions

Units:mm

