





Specifications	AirLive M2M-4GPoE
----------------	-------------------

Model	M2M-4GPoE	
WAN	LTE Band:Band B1/B2/B3/B4/B5/B7/B8/B28/B40 (S2 version) 3G :B1/B2/B5/B8 (S2 version) 1 RJ45 Gigabit WAN Port	
LAN Port	Gigabit (Auto-MDI/MDI-X) UTP Port x 4 with 802.3at/af PoE output	
PoE Budget	Up to 120W	
WiFi	802.11 a/n/ac 2T2R 5Ghz or 2.4Ghz	
Extension Interface	DI/DO x 1 RS232/RS485x1 (4Pin Terminal Block)	
Antenna	2 X 3 dBi SMA Onmi Antenna (LTE)	
Software	Ethernet/ 3G,4G Load Balance or FailOver SIM-SIM failover IPv6 - 6-in-4 - 6-to-4 Multi-SSID WPS WMM VLAN NAT - ALG - Special AP - DMZ Host - Virtual Server - PPTP - L2TP - IPsec Passthrough DDNS Pacaket Filters URL Blocking Web Content Filter MAC Address Control Application Filter QoS and Band Width Management	VPN Tunneling - IPsec - PPTP - L2TP - GRE VPN - L2TP Over IPsec VPN Scenario - Site to Site - Site to Host - Host to Site - Host to Host - Dynamic VPN Redundancy - VRRP Captive Portal Status & Statistics Scheduling FW upgrade Backup & Restore Setting
Management	Web Telnet SNMP SMS TR-069	
Power Input	DC 48~54V	
Temperature	Operating - -30~70°C	Storage - -40~85°C
Humidity	Operating - 10~90% (Non-Condensing)	Storage - Max.95% (Non-Condensing)
Dimension and Certification		
Dimensions (LxWxH)	62x125x160mm(LxWxH)	
Certification	TBD	

Ordering Information:
-----------------------

<b>AirLive M2M-S2</b> Industrial LTE Gateway with Serial Port
---